

# Space-Based Sensor Enhancement By Signal Processing

Bob Nellums

July 15, 2014

# Acknowledgements

- JSC/ES: George Studor (Overall)
- JSC/KX: Michael Rollins, Ed Oshel, Donn Liddle (Image Analysis and Image Processing)
- JSC/EV: Michael Grygier (Vibrometry)
- LaRC: Eric Maderas (Radar)
- GSC: Justin Cassidy (VIPIR)
- Sandia National Laboratories (LDRI)
- Pacific Northwest Laboratories (Radar)

# Examples to be covered

1. “**SURVEY**” Inspection to Detect Damage
  - Rapid, preplanned coverage of large areas
  - Detect possible holes, cracks for focused inspection
2. “**FOCUSED INSPECTION**” to Quantify Damage
  - Extended-time coverage of detections
  - Measure damage depth/volume, especially at critical subsurface layers
3. “**VIBROMETRY**”
  - Remotely measure modal response of structure
    - Validate structural models
    - Detect damage-induced changes

# Application 1: SURVEY

- Closed Circuit TV video was used for Shuttle Survey
  - Rapid area coverage, real-time downlink, many remote camera stations (including SSRMS)
- Desire for higher resolution is constrained by existing data transmission hardware
  - Incentive to enhance imagery via software, if possible
- Examples in following slides
  - Shuttle Leading Edge Inspection, STS114 – STS135
    - LDRI video (an intensified camera)
  - International Space Station video
    - Color TV video
    - VIPIR video


# Image Enhancement Examples

- Pixel Gain and Offset Correction
- Camera distortion correction
- Motion stabilization and multiframe averaging
- Inverse Blur correction
- Super resolution


# PIXEL GAIN AND OFFSET CORRECTION

Applied to LDRI CAMERA

RAW



CORRECTED





# DISTORTION CORRECTION

- Distortion causes straight lines to appear curved
- Desired for photogrammetry or highly distorted images
- Corrected using calibrated distortion parameters
  - Brown's Distortion Model
  - Laboratory calibration or data-driven



# Multi-frame Averaging + Contrast Stretching (LDRI Camera)

- Normal pixel intensity is 8-bits, with noise
- Averaging improves intensity resolution with fractional resolution and reduced noise




- On orbit inspection of OV-103 Port Panel 10 (RCC)




# Multi-frame Averaging + Filtering (LDRI Camera)

- Reduced noise/aliasing improves spatial resolution
- Enables inverse filtering to improve blur




**SINGLE FRAME**



**REGISTERED AVERAGE OF  
32 MOVING FRAMES  
AFTER INVERSE BLUR FILTER**


# Multi-frame Averaging + Filtering (LDRI Camera)

P6 Truss of the International Space Station, STS97




# Multi-frame Averaging + Filtering (LDRI Camera)

1951 USAF resolution up by  $\sim 26\%$  (2 elements)






# POTENTIAL OF SUPER RESOLUTION




(simulated 30x30 data)



1x1 Raw Image




2x2 subsampling




8x8 + Inverse Blur Filter



# SUPER RESOLUTION OF ISS VIDEO



MULTIFRAME AVERAGE  
WITH SUBSAMPLING



FULL SIZE

SINGLE FRAME



# POTENTIAL OF CHANGE DETECTION (Background Subtraction)



- Sensitive to nearly invisible features
  - Light scuff marks and sub-pixel objects
  - Good results require close positioning, and minimizing lighting changes


# “Blink” Change Detection

STS 130 Inspection, LDRI Camera



# Change Detection

STS135 Inspection, LDRI Camera



This slide is unfinished, but will show the difference in the above images




# Data-Driven Background Subtraction

- Estimate background and subtract from image
  - Estimate background as narrow-band spectral peaks

RAW IMAGE

BACKGROUND  
ESTIMATION


BACKGROUND  
SUBTRACTION




Tian, Xuwen: "Data-driven textile flaw detection methods"

# Change Detection Applied to RADAR


- Radars can measure complex reflectance from scene “pixels”
- Radar images (left, center) show reflectance **magnitude**
- CCD image (right) shows change in complex reflectance
  - Can be much more sensitive to change than magnitude
- Might this enable radar to be used for SURVEY?
  - Could sub-pixel, sub-wavelength damage be detected?



Pre-activity image



Post-activity image



CCD image

# Application 2: **FOCUSED INSPECTION**


## Measure Damage Size and Depth

### Camera Suitability

- Incentive to use Cameras
  - Existing resource, robotic flexibility
  - High resolution, visual context
- Issues with Cameras
  - Depth measurement required
  - Non-penetrating, limited to line-of-sight
  - Illumination difficulty into narrow openings
  - Tradeoff between Resolution and Depth of focus

# RESOLUTION VS. DEPTH OF FOCUS

(500nm Wavelength)



# Examples Yielding 100um Resolution, 20mm DOF






(FOCAL LENGTH AS REQUIRED)

- 50mm (2") Standoff: 0.25-0.50mm Lens Diameter
  - "Borescope" type of camera
  - Requires special prox ops approval
- 500mm (20") Standoff: 2.5-5.0mm Lens Diameter
  - Nikon or video camera at high F/#, small telephoto lens
  - Dextre prox ops
- 1m (3.1') Standoff: 5.0-10mm Lens Diameter
  - SSRMS prox ops
- 10m (16') Standoff: 50-100mm Lens Diameter
  - Nikon or video camera at low F/#, large telephoto lens



# Hypervelocity Impacts to Sample Silica Re-entry Tile (#3)

## Entry Holes and X-ray CT Images




(Courtesy NASA/KX)

# COLORIMETRY (Nikon Camera)

- Color in a critical layer can be a sensitive damage indication
- In this case, the critical layer is colored red


ID2 RAW IMAGE




RAW ENLARGEMENT



CR COLORSPACE COMPONENT




CR ENLARGEMENT



# FLUORESCENCE

- The critical damage site may not always be visible
- Fluorescent material from a critical layer can be a sensitive indicator in the visible debris




(Source: Michael Rollins, JSC Image Sciences)




# 3D Evaluation

- Goal: Measure size and depth of ID1, ID2, ID3
- Data Base: 2-D camera images, multiple poses
  - Borescope Camera (~1" standoff)
  - Nikon Camera (~20" standoff)
- Depth determination
  - Using parallax: "Structure From Motion"
  - Using focus: "Structure from Focus"


# Borescope Testing




**Borescope Configuration.** Pulnix camera (at right) is optically coupled to distal end of 8-mm borescope (at left). Illumination is coupled through flexible light guide (at center).




Illumination ring  
surrounding input window



 = 20-40mm range, 1mm aperture, 60° FOV


# ID1 Structure From Motion

- 20mm normal standoff
- Center, 4mm up, down, left, right



**TRUTH DATA**

(Studor/Olstad/Smith/Rollins: "MMOD Inspection and Detection Study and Recommendations" )



**BORESCOPE SFM DATA**

(PhotoScan software analysis )

# ID1 Structure From Motion

- 20mm normal standoff
- Center, 4mm up, down, left, right





**TRUTH DATA**  
(Courtesy Michael Rollins, JSC Image Sciences)



**BORESCOPE SFM DATA**  
(PhotoScan software analysis )

# ID2 Structure From Motion

- 17-23mm axial standoff
- Conical scans at 30,40,50°
- 10° azimuth steps





**TRUTH DATA**  
(Studor/Olstad/Smith/Rollins: "MMOD Inspection  
and Detection Study and Recommendations" )




**BORESCOPE DATA RECONSTRUCTION**  
(PhotoScan software analysis )

# ID2 Structure From Motion

- 17-23mm axial standoff
- Conical scans at 30,40,50°
- 10° azimuth steps



**TRUTH DATA**  
(Courtesy Michael Rollins, JSC Image Sciences)




**BORESCOPE DATA RECONSTRUCTION**  
(PhotoScan software analysis )




# ID3 Structure From Motion

- 8-10mm axial standoff
- Conical scans at 30, 40°
- 10° azimuth steps



**TRUTH DATA**

(Studor/Olstad/Smith/Rollins: "MMOD Inspection and Detection Study and Recommendations" )




**BORESCOPE DATA**


(PhotoScan software analysis )

# ID3 Structure From Motion

- 8-10mm axial standoff
- Conical scans at 30, 40°
- 10° azimuth steps



**TRUTH DATA**  
(Courtesy Michael Rollins, JSC Image Sciences)



**BORESCOPE DATA**  
(PhotoScan software analysis )




# Nikon Testing



Nikon DX2s camera with Micro-Nikkor 105mm f/2.8 lens and ring illuminator (at right) viewing AETB-8 target mounted on computer-controlled, translation and rotation stage (left).

## Optical Resolution

500nm Wavelength




= 300-500mm range, 37 mm aperture, 5.5um pixels




= 500mm range, 3 mm aperture, 5.5um pixels (4-pixel blur)

# Borescope vs Nikon Comparison

**BORESCOPE FROM 10mm (0.4")**




**NIKON FROM 0.44m (17.3")**



# ID3 Structure From Motion


(Nikon Dataset Limited to just 5 views)

- 266mm (17.3") axial standoff
- 45° incidence
- 5 images at 20mm steps



**TRUTH DATA**

(Studor/Olstad/Smith/Rollins: "MMOD Inspection and Detection Study and Recommendations" )




**NIKON DATA**

(PhotoScan software analysis )

# ID3 Structure From Motion


(Nikon Dataset Limited to just 5 views)

- 266mm (17.3") axial standoff
- 45° incidence
- 5 images at 20mm steps



**TRUTH DATA**

(Studor/Olstad/Smith/Rollins: "MMOD Inspection and Detection Study and Recommendations" )




**NIKON DATA**

(PhotoScan software analysis )



# STRUCTURE FROM FOCUS



# 3D from 2D Conclusions

- Proper illumination and lens are crucial
- Over-the-counter Structure From Motion software performs well
  - Further validation needed
    - More examples, difficult cases
    - Scaling and dimensional comparisons with truth
  - Structure from Focus also appears feasible
    - Was investigated in less detail
    - May complement SFM
- Potential improvement by combining focus, motion algorithms
  - Results presented here use either but not both simultaneously
- Best results require many views
  - Easily configured using robotics
  - Could be performed with either video or Nikon
  - Processing in near-real time
    - ~10min on laptop
    - Estimated 30s on high performance desktop



# RADAR Observations

- Lower frequencies penetrate better
- Return from reflective backing preferred to direct return
- Circular polarization preferred to linear/none
- Polarization ratio preferred to magnitude of either polarized or unpolarized return

“Insitu Damage Imaging of Inflatable Structures”

Studor, Madaras, Nellums, McMakin



NASA test article

# 10-20 GHz Radar, Circularly Polarized




(Courtesy Douglas McMakin, PNNL)

R-L




R-R

R-L / R-R

Direct Return  
from Undamaged  
Surface




Reflected  
Return from  
MLI Backing



# APPLICATION 3: VIBROMETRY

Identify modes to validate codes and detect changes




## Approach:

Adjust each video frame, using a motion model, to best match a reference image.

## Key Need:

Adequately identify more modes

**DX,DY Displacement, Blanket Box of S43A-SAW, Frames 0-16828**



("Response of ISS S4-3A Solar Array Wing to Reboost 6/17/2011" , courtesy Donn Liddle, NASA/JSC Image Sciences)


# VIBROMETRY CONCLUSIONS

## Potential Areas for Improvement


- Registration Algorithm
  - Especially regarding motion interpolation
- Video Error Correction
  - Many systematic issues with downlinked video
- Motion Model Degrees of Freedom
  - Current model is offset only
- Reference Image Accuracy and Resolution
  - Effect of aliasing and desire for super-resolution

# Spectral Comparison of Results

Spectrum of  
Existing Analysis  
(floor = 0.01 pixels/root-Hz)



Spectrum of  
Refined Analysis  
(floor = .0024 pixels/root-Hz)



END